

FORMULATED FOR ADDITIVE MATERIALS.

As the pioneer of the automated post-printing industry, PostProcess Technologies' patent-pending software, hardware, and chemistry solutions for 3D printed parts are unmatched. Our innovation extends to our proprietary detergents and media that have been developed for high-performance and safe handling. Learn more below about how PostProcess chemistry technologies work as a part of our precise solutions to drive faster throughput and more consistent results.

SUPPORT REMOVAL (SR) SOLUTIONS

PostProcess' pre-mixed detergents optimize the removal of supports while leaving the build material in perfect condition. Our patent-pending chemistries are formulated for all 3D print materials and technologies and specified to achieve the customer's desired cycle time and end product characteristics.

| DETERGENT: | SUBMERSION SYSTEMS | SPRAY SYSTEMS | ANTI FOAMING AGENT: All Materials |
|--------------------------|---------------------------|----------------------|--|
| Polyjet Materials | <i>PLM-101-SUB</i> | <i>PLM-101-SPRAY</i> | <i>AUX-001-DEFOAM</i> |
| SLA Materials | <i>PLM-402-SUB</i> | <i>PLM-401-SPRAY</i> | <i>AUX-002-DEFOAM</i> |
| FDM Materials | <i>PLM-201-SUB*</i> | <i>PLM-201-SPRAY</i> | |

**North America Only*

SURFACE FINISHING (SF) SOLUTIONS

Our surface finishing media, available in different density and grit, is designed to accurately deliver the correct amount of energy to produce the desired end result. With our offering of Ceramic Angle Cut Triangle Media (M-CAT), Polyester Abrasive Media (PAM), and Ceramic Tristar Media (M-CTS) we can ensure the desired finish for all print materials and end product surface roughness (Ra) requirements.

| MEDIA: | | Grit | Grit Size | Finish | Media Attrition Rate | MEDIA CLEANING AGENT: All Materials |
|-------------------------|--------------|-------------|------------------|---------------|-----------------------------|--|
| Polymers, Metals | <i>M-CAT</i> | Coarse | Large | Matte | Medium | <i>PLM-001-SURF</i> |
| Polymers | <i>PAM2</i> | Fine | Medium | Matte | Low | |
| Polymers, Metals | <i>M-CTS</i> | Fine | Medium | Matte | Low | |

**optional*

HYBRID SOLUTIONS - SUPPORT REMOVAL & SURFACE FINISHING

Tackling both support removal and surface finishing in one compact footprint, our Hybrid PostProcess™ DECI Duo™ was developed to address the most complex and rugged of today's additive manufacturing materials. Our exclusive media, combined with our additive-formulated chemistries, produced at the right mixture and discharged at an exacting rate over the surface, ensure superior support removal and surface finishing. The Duo is the workhorse of post-processing, developed for high-performance and optimized to use our patent-pending detergents and media.

DETERGENT:

PLM-001-DUO

SUSPENDED SOLIDS:

| | Grit | Grit Size | Finish | Solids Attrition Rate | Average Result Time |
|--|-------------|------------------|---------------|------------------------------|----------------------------|
| AS-SS (Abrasive Ferrous Metal) | Coarse | Large | Matte | Medium | 15 - 20 minutes |
| AS-ALO (Abrasive Non-Ferrous Metal) | Fine | Small | Matte | High | 5 - 7 minutes |
| PS-SS (Polishing Ferrous Metal) | Extra Fine | Large | Polish | Medium | 15 - 20 minutes |
| PS-ZIR (Polishing Ceramic) | Extra Fine | Small | Polish | Low | 15 - 20 minutes |

ADDITIVE FORMULATED. PRODUCTION READY.

All of PostProcess' patent-pending chemistry technologies have been designed with careful consideration of safety and handling. Because our proprietary detergents are already mixed, there is no chance of incorrectly mixing a batch of detergent, versus other offerings which must often be mixed on-site. Our chemistries utilize low concentrations of several conventional chemicals in unique combinations, as compared to other detergent options with higher chemical concentration levels.

For our Support Removal and Surface Finish Series, we offer our detergents in pre-mixed 5 gallon and 55 gallon containers. Concentrated versions are also available for our spray systems.

For our Surface Finish Series, we offer our media in 50 pound plastic containers with molded-in handles for easy unload and storage. Our media has been formulated and tested to have the lowest attrition rates in the additive manufacturing industry.

POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA
+1.866.430.5354 info@postprocess.com

POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France
+33 (0)4 22 32 68 13

NOTE: PostProcess Technologies detergents are specifically formulated chemistry for maximized 3D printed support removal efficiency. It is recommended that the equipment be located in a well ventilated room. Specific ventilation requirements can vary widely due to size of the install room, existing ventilation (positive or negative) and differences in individual sensitivities to airborne scents or fragrances. For more information on the safe use of PostProcess detergents refer to the SDS for the specific detergent used.